

Electric / Gas Pressure Frye

- High quality stainless steel body, aluminum lid, makes the machine stable with elegant appearance. S.S.304 rectangular fry pot promotes more even cooking.
- Build-in oil filtration system can filter and return hot oil in less than four minutes with no extra pumps or pans and no handling of hot oil, provides quick, easy and safe cooking oil filtration.
- Standard electro-mechanical control with easy to use temperature and timer controls. Automatic pressure

- release valve to ensure the safety.
- Pre-programmable of 10 different cook cycles for quick and easy preparation of various menu items, as well as automation, energy-saving, filtration and cook management features.
- Lower cooking oil consumption, very low oil absorption into food.
- With programmable panel. With oil filter.



Code: 0300103940



Code: 0300103941



Code: 0300103942

Code	Model	Dimension(mm)	Capacity	Power	Voltage	Gas Consumption	NW
0300103940	PPF-25EPO	460 x 970 x 1220	25L	12.5 KW	380 V		135 kg
0300103941	PPF-25GPO	460 x 1000 x 1240	25L	0.47 KW	220V	About 0.48 kg/h	165 kg
0300103942	PPF-55EPO	1140 x 620 x 1550	55L	17 KW	380 V		310 kg

Electric / Gas Open Fryer

- Built-in automatic oil filter system, easy to use and high efficient.
- The computer control panel ,elegant,easy to operate,accurately control time and temperature.
- High efficiency heating elements, can be ready for food in short time.
- Shortcuts to save memory function, constant time and temperature.
- With programmable panel. With oil filter.



Code: 0300103946



Code: 0300103944



Code: 0300103947



Code: 0300103945



Code: 0300103948



Code: 0300103949

Code	Model	Dimension(mm)	Capacity	Power	Voltage	Gas Consumption	NW
0300103944	POF-321EPO	440 x 900 x 1180	35L	12.5 KW	380 V		115 kg
0300103945	POF-322EPO	880 x 900 x 1180	2 x 35L	2 x 12.5 KW	380 V		220 kg
0300103946	POF-323EPO	1320 x 950 x 1180	3 x 35L	3 x 12.5 KW	380 V		260 kg
0300103947	POF-321GPO	440 x 950 x 1180	25L	0.47 KW	220 V	About 0.48 kg/h	135 kg
0300103948	POF-322GPO	880 x 950 x 1180	2 x 25L	2 x 0.47 KW	220 V	About 0.96 kg/h	260 kg
0300103949	POF-323GPO	1320 x 950 x 1180	3 x 25L	3 x 0.47 KW	220 V	About 1.44 kg/h	300 kg

Electrical Marinator with Vacuum Pump

- Stainless steel structure
- Stainless steel tank with leak proof gasket
- Vacuum pump to marinate meat much faster
- 4 swivel castors for mobility
- Timer control inside
- Buzzer alarms when marinating cycle is finished
- Vacuum meter to monitor inside
- On/off switch to control vacuum pump
- Two plastic containers (one perforated pan)
- Deeper flavor profile can be infused inside proteins
- Marinate on demand to avoid waste



Code: 0300101823

Code	Model	Dimension(mm)	Capacity	Timing	Power	Voltage	NW
0300101823	EM-36V	950 x 500 x 940	36 KG	10 Min	250W	230V	78kg

Electrical Marinator without Vacuum Pump

- Stainless steel structure
- Stainless steel tank with leak proof gasket
- 4 swivel castors for mobility
- Timer control inside
- Buzzer alarms when marinating cycle is finished
- Two plastic containers (one perforated pan)
- Deeper flavor profile can be infused inside proteins
- Marinate on demand to avoid waste



Code: 0300102068

Code	Model	Dimension(mm)	Capacity	Timing	Power	Voltage	NW
0300102068	EM-36	950 x 500 x 940	36 KG	10 Min	250W	230V	62kg

Holding Cabinet / Pass Through Holding Cabinet

- Stainless Steel Body.
- Magnetic Door Handle.
- Adjustable and Detachable Shelf .
- Heavy Duty Castors, Easy front-mounted control.
- Push Pull Side Handle, Conveniently move the machine .
- 360° Hot air circulation, Consistent temperature control.
- Vertical distance of tray slides: 100mm
- Power: 2 KW, Voltage: 220 V
- With LED lights. With tray no grid.
- America size pan. Tray Size: 460x660 mm.



Code	Model	Dimension(mm)	Capacity	Door	NW
0300103962	HC-6AS-S	610 x 790 x 995	6 Trays	One side open, glass door	98 KG
0300104034	PHC-6AS-2S	610 x 790 x 995	6 Trays	Two side open, Front glass door, back glass door	98 KG
0300103950	HC-6AS	610 x 790 x 995	6 Trays	One side open, three flip-open glass door	98 KG
0300103951	PHC-6AS-2	610 x 790 x 995	6 Trays	Two side open, Front three flip-open glass door, back glass door	98 KG
0300103952	PHC-13A	670 x 610 x 1950	13 Trays	One side open, glass door	255 KG
0300103953	PHC-13A-2	670 x 610 x 1950	13 Trays	Two side open, Front glass door, back glass door	255 KG

Pass Through Mobile Holding Cabinet

- Stainless steel structure, four doors design
- Two blowers on the top for better hot air circulation
- Digital thermostat
- Self-locking latch
- Good insulation to improve holding efficiency
- 110°C EGO thermostat controlled, durable and robust
- Water-proof on/off switch
- Double durable stainless steel round heating element
- Forced air circulation with special baffle plate
- Stainless steel lock
- Four swivel heavy duty 6" castors with brake
- Recessed hand-grasping handle on both sides
- Rubber seal on the doors
- Water tray on the top to keep food humidity when needed
- GN2/1 wiring grid optional
- Capacity: 14 x America size pan (450x650mm)
- Vertical distance of tray slides:100mm (14 level)
- Stainless steel heating elements



Code	Model	Dimension(mm)	Capacity	Power	Voltage	Temp.	NW	GW
0300102458	PTHC-14	636 x 786 x 2000	14 x (450 x 650mm)	2 KW	220 ~ 240 V	30~110°C	120KG	150KG

Holding Cabinet Meat Patty Warmer

- Doubles the holding time while keeping food fresh.
- Alphanumeric displays for each pan
- Program up to six different menus.
- Independent temperature setting
- Imported food grade baking pans with rack.
- Insulated handle for easy access.



Code	Model	Dimension(mm)	Capacity	Power	Voltage	NW
0300103954	RB-1-2S	560 x 440 x 200	1 layers 2 trays	0.6 KW	220 V / 50Hz	23 KG
0300103955	RB-2-2	360 x 440 x 320	2 layers 2 trays	0.6 KW	220 V / 50Hz	23 KG
0300103956	RB-2-4S	560 x 440 x 320	2 layers 4 trays	0.8 KW	220 V / 50Hz	27 KG
0300103957	RB-2-6S	750 x 440 x 320	2 layers 6 trays	1 KW	220 V / 50Hz	35 KG
0300103958	RB-2-8S	920 x 440 x 320	2 layers 8 trays	1.8 KW	220 V / 50Hz	39 KG
0300103959	RB-3-9S	750 x 440 x 520	3 layers 9 trays	2.4 KW	220 V / 50Hz	45 KG
0300103960	RB-4-4	500 x 600 x 560	4 layers 4 trays	2 KW	220 V / 50Hz	35 KG

Breeding Table



Code	Model	Dimension(mm)	Power	Voltage	NW
0300104032	BTGU-1220A	1150 x 450 x 850	120W	220 V	50 KG
0300104033	BTGU-1220B	1150 x 760 x 850	120W	220V	55 KG