



Durable Construction and Ingenious Design - Convection Oven by MOFFAT New Zealand

Turbofan convection oven systems offer portability to suit any application, an expandable platform with a wider range of oven footprints, increased tray loading capacity and smart door design for safety. Coupled with the 30 series' matching prover and holding cabinet, Turbofan offers more features within its DNA.

Turbofan is produced in Moffat's new state of art production facility in Christchurch, New Zealand.

TURBOFAN FEATURES – PRECISION DIGITAL CONTROL

- Multi Stage – 3 stage cooking and baking with stage and alarms
- Electronic Time & Temperature – knob driven convenience with electronic accuracy
- Manual Model – simple selection of time and temperature control
- Product Programs – 20 cooking/baking profiles can be stored in the program mode
- Digital Display – easy view settings with electronic accuracy
- Action Keys – quick control of oven functions/models
- Moisture Control – steam injection mode (5 levels) and manual injection
- Core Temp Control – core temperature cooking (optional core probe kit E32 & E33 only)

E23D3 Series - 3 Tray Half Size Electric Convection Oven



E23D3

W 610 x D 642 x H 607 mm
3 Tray 460 x 330 / GN2/3 capacity
85 mm tray spacing
Volt. 230/1/50, E. Pow. 3.00 kW

Standard Features of E23:

- Bi-directional reversing fan system
- Halogen oven lamp
- Dia. 180 mm full stainless steel oven fan
- 3 oven wire racks supplied

Features of E23D3:

- Compact 610 mm width
- Digital display time and temperature controls
- Large easy view 20mm high displays
- Electronic timer
- Manual mode and program mode
- 20 programs with 3 stage cooking and stage end alarms
- Steam injection mode (5 levels) and manual injection

E31D4 - 4 Tray Half Size Electric Convection Oven



E31D4

W 810 x D 616 x H 810 mm
4 Tray GN1/1 capacity
80mm tray spacing
Volt. 230/1/50, E. Pow. 3.10 kW

Standard Features of E31D4

- Quick-select grill mode
- Single direction low-velocity fan
- 2.8kW heating in bake mode / 2.0kW grill elements
- Halogen oven lamps
- 4 oven wire racks supplied

Features of E31D4:

- Digital display time and temperature controls
- Large easy view 20mm high displays
- Electronic thermostat control
- Electronic timer
- Manual mode and program mode
- 20 programs with 3 stage cooking and stage end alarms

E931M - 4 Tray Half Size Electric Convection Oven and 4 Element Cooktop

MOFFAT®

E32D5 & G32D5 - 5 Tray Full Size - Electric & Gas Convection Oven



E32D5

W 735 x D 810 x H 730 mm
5 Tray 460 x 660 mm Capacity
85mm tray spacing
Volt. 230/1/50, E. Pow. 6.5 kW

- 5 18" x 26" / 460 x 660 full size sheet pan capacity
- 5 600 x 400 tray capacity
- 85mm tray spacing
- Compact 735mm width
- Moisture injection mode (5 levels)
- 2 speed bi-directional reversing fan system
- 6.5kW heating
- Dual halogen oven lamps
- 5 oven wire racks supplied
- Digital display Time and Temperature controls
- Large easy view 20 mm high displays
- Electronic timer
- Manual mode and Program mode
- 20 programs with 3 stage cooking and stage end alarms



G32D5

W 735 x D 810 x H 910 mm
5 Tray 460 x 660 mm Capacity
85mm tray spacing
Volt. 230/1/50, E. Pow. 0.12 kW
LPG, G. Pow 33,200 BTU/hr

- 5 18" x 26" / 460 x 660 full size sheet pan capacity
- 5 600 x 400 tray capacity
- 85mm tray spacing
- Compact 735mm width
- 10A plug-in cordset fitted
- Electronic burner ignition and safety control system
- Water injection mode
- Bi-directional reversing fan motor
- 33,200 BTU/hr patented infrared burner system
- Dual halogen oven lamps
- 5 oven wire racks supplied
- Digital display Time and Temperature controls
- Large easy view 20 mm high displays
- Electronic thermostat control
- Electronic burner ignition and safety control system
- Manual mode and Program mode
- 20 programs with 3 stage cooking and stage end alarms

P8M & P12M - Dual Function Proofing and Holding Cabinet



P8M

W 735 x D 810 x H 914 mm
8 Tray 460 x 660 mm Capacity
76mm tray spacing
Volt. 230/1/50, E. Pow. 1.50 kW



P12M

W 735 x D 810 x H 1129 mm
12 Tray 460 x 660 mm Capacity
74mm tray spacing
Volt. 230/1/50, E. Pow. 1.90 kW

- Can function for both prover or holding cabinet
- Full Double Skin Construction
- Auto Water Fill System
- Off / Prove / Hold Mode Selection
- Low Velocity Circulation Fan System
- Humidity Level Control
- Dual Halogen Cabinet Interior Lamps
- 76mm Dia. Castors - 2 front dual wheel and swivel lock and 2 rigid rear castors